

ROWAFLEX® X 572

Emulsifier for thermoplastic adhesives

Type	Emulsifier
Chemical character	Long-chain ethoxylated fatty alcohol
Density	96 kg/m ³
pH value	7
Ionogenity	non-ionic
Appearance	Clear to cloudy liquid
Product viscosity	90 mPa.s (EN 12092 Brookfield (23°C/60rpm))
Properties	<p>ROWAFLEX® X 572 is an emulsifier for all common thermoplastic powders like copolyamides, copolyester, high-and low density polyethylene and polyurethane. It has highly efficient dispersing properties.</p> <p>Pastes with ROWAFLEX® X 572</p> <ul style="list-style-type: none"> • are easy and fast to prepare • are having excellent running properties • are free of organic solvents and enviromentalfriendly • provides good adhesion values for different fabrics • due to the good dispersing properties only low quantity is required
Application	<p>ROWAFLEX® X 572 is a high efficient emulsifier for thermoplastic hotmelt powders.</p> <p>For 100 kg ready made paste (35 % solid content) only 1 kg of ROWAFLEX® X 572 is required. It is easy and fast disperable in cold water.</p>

Version: 03.05.2022

Die vorstehenden Angaben entsprechen dem derzeitigen Stand unserer Erkenntnisse und Erfahrungen. Wir beraten Sie damit unverbindlich und bitten Sie, alle Angaben über die Verwendung unserer Produkte auf die bei Ihnen vorliegenden Verhältnisse abzustimmen und den verwendeten Materialien anzupassen.

All information provided is based on our experience and current know-how but is given without guarantee and obligation. Recommendations on the application and use of our products should be adapted to the particular conditions and other materials employed.

ROWAK AG
Hadlaubstraße 66
CH 8006 Zürich

Tel +41 43 300 53 33
Fax +41 43 300 53 35

www.rowak.ch
info@rowak.ch

Certified Quality
Management System

ROWAK AG
Schmittenstraße 21
D-79771 Klettgau

