

# ROWAFLEX® X 800

## Acqueous Polyurethane solution

<b>Type</b>	Dispersions
<b>Chemical character</b>	Polyurethane
<b>pH value</b>	7
<b>Appearance</b>	Opaque white liquid
<b>Product viscosity</b>	500 - 600 mPa.s (Brookfield)
<b>Properties</b>	<ul style="list-style-type: none"> <li>• Elongation at break: 780 %</li> <li>• Tensile strength: 30 mPa.</li> </ul>
<b>Application</b>	ROWAFLEX X 800 provides excellent adhesion to natural and synthetic fabrics. It has very good hydrolysis and washing resistance. ROWAFLEX X 800 can be used as adhesive or coating for transfer printing as well as coating applied in direct printing. If the viscosity needs to be increased, ROWAFLEX TH 3 can be added.

Version: 03.05.2022

Die vorstehenden Angaben entsprechen dem derzeitigen Stand unserer Erkenntnisse und Erfahrungen. Wir beraten Sie damit unverbindlich und bitten Sie, alle Angaben über die Verwendung unserer Produkte auf die bei Ihnen vorliegenden Verhältnisse abzustimmen und den verwendeten Materialien anzupassen.  
All information provided is based on our experience and current know-how but is given without guarantee and obligation. Recommendations on the application and use of our products should be adapted to the particular conditions and other materials employed.

Certified Quality  
Management System

